

FENCE WIND/PRIVACY SCREENS

PREMIUM WOVEN POLYPROPYLENE & KNITTED HDPE FABRIC FULLY TAPPED AND GROMMETTED EVERY 18" WITH ENHANCED UVI PROTECTION



WOVEN

- Tightly woven high quality polypropylene fabric
- Approx. ±95% blockage
- Ideal for maximum privacy, aids in wind blockage
- Built to last--high quality UVI additive prevents fading
- Dark green color
- 50' long x 5'8" wide, fits snug on 6' chain link fence
- 1.5" black HD border tape double sewn around all sides
- Border tape reinforced grommets every 18"
- Double grommets on the corners for added strength
- Weather, mold, mildew & tear resistant
- Easy installation with zip ties or hog ring clips

KNITTED

- High quality, knitted HDPE mesh fabric
- Approx. ±80% blockage
- Better choice for windy areas
- Built to last--high quality UVI additive prevents fading
- Green & black color available
- 50' long x 5'8" wide, fits snug on 6' chain link fence
- Reinforced border tape & brass grommets every 18"
- Weather, mold, mildew & tear resistant
- Easy installation with zip ties or hog ring clips
- Available in 6'x150' raw material rolls (no border tape)

****ASK YOUR SALES ASSOCIATE FOR TEMP. CHAIN LINK PANEL & STAND AVAILABILITY****

See reverse side for fabric specifications.

FABRIC SPEC. SHEETS

WOVEN

UV ENHANCED, WOVEN POLYPROPYLENE	ASTM TEST METHOD	PRODUCT #'s PS-50, PS-14, PS-12, PS-10
CONSTRUCTION		10 X 10
COLOR		DARK GREEN
FABRIC WEIGHT		3.5 OZ SQYD
GRAB TENSILE	D4632	150 LBS
GRAB ELONGATION	D4632	>18%
UV RESISTANCE	AFTER 500 HR EXPOSURE	>80%
PUNCTURE RESISTANCE	D4833	80 LBS
TRAPEZOID TEAR	D4833	60 LBS
MULLEN BURST	D3786	350 PSI

KNITTED

UV ENHANCED, KNITTED HIGH DENSITY POLYETHYLENE	ASTM TEST METHOD	PRODUCT #'s PS-KG0650, PS-KG0612, PS-KG0850. PS-KG0812
CONSTRUCTION		13 X 13
COLOR		DARK GREEN & BLACK
FABRIC WEIGHT		4.7 OZ SQYD
UV RESISTANCE	AFTER 500 HR EXPOSURE	>80%
BREAK STRENGTH		500LBS FT
CRYSTALLINE MELT POINT		133°c
FLAMMABILITY POINT		364°c